The background of the image is a blurred, abstract pattern of light streaks in shades of yellow, green, and blue, creating a sense of motion and energy.

**NOWATT
LIGHTING**

**ARCHITECTURAL
SOLAR
LIGHTING**



AUTONOMOUS, INTELLIGENT AND CONNECTED LIGHTING
AVAILABLE IN 3 LINES

MARKING

LIGHTING

POWERING



tomorrow, most lighting projects will be solar and connected

We are lighting manufacturers. We thought of products that get rid of energy and installation costs, simple and friendly, that we take out of the box and start up in one click.

Thanks to technological leaps, the efficiency of our solar lighting devices is boosted by the efficiency gains of their various components.

#lightupeverywhere




**NOWATT
LIGHTING**

100% AUTONOMOUS

REMOTE CONTROL

THE INTELLIGENT



TURN IT ON, IT UNDERSTANDS INSTANTLY ITS
POSITION ON THE GLOBE

IT MANAGES ITS LOAD AND CALCULATES AN
OPTIMAL POWER ALL THE YEAR

TAKING INTO ACCOUNT LATITUDE, SEASON AND
WEATHER CONDITIONS

ONE MILLION COLORS

CHOOSE YOUR LIGHT SCENARIO

1



6 HOURS OF CONTINUOUS LIGHTING FROM
SUNSET



2



4 HOURS FROM THE SUNSET AND 2 HOURS
BEFORE SUNRISE



3



MOTION SENSOR FROM SUNSET TO SUNRISE




4



YOUR CUSTOMIZED SCENARIO



CHOOSE AMONG 1 MILLION COLORS




CREATE DIRECTLY
FROM YOUR
SMARTPHONE
WITH OUR APP



The abacus below represents the number of cycles estimated for the Lithium Iron Phosphate batteries (LFP, LiFePO4), depending on the discharge power and the DOD. The testing conditions are those of a laboratory (constant temperature of 25°C, charging and discharging power constant).

LIFESPAN BATTERY



In a standard environment, and for cycles done at 1C, the abacus gives an estimated number of cycles for the LiFePO4 of:

- 2000 cycles at 100% of DOD 5 years
- 3000 cycles at 80% of DOD 8 years
- 8000 cycles at 55% of DOD 22 years

After the number of cycles done, the batteries still have a capacity superior to 80% of the original capacity.





Marking

Crystal studs

Lighting

Onyx Projectors

Onyx Bollards

E-Onyx Stud

Onyx Column

Powering

Onyx Power

Novelties

Solar Marking Firefly

Walls and Floors

Other productions

Appendices

Lifespan and maintenance


Round Crystal Studs installation manuals

Brief story of shade

PRESENTATION
CONTENT



**MARKING
CRYSTAL STUDS
PROJECTS**



Maison Jean Prouvé
Marking
Friche de l'Escalette – Marseille
- France

Lighting designer:

Architect:

Delivery:
June 2017

Products:
PLR1

NOWATT
LIGHTING



LA POSSESSION I
Marking of a cycle track
LA REUNION, France


Lighting designer:
Agence Scène publique

Landscaper: Leu Réunion

Delivery:
June 2017

Products:
160 PLR1

NOWATT
LIGHTING



Place Basse
Marking of the forecourt of
La Défense – Paris - France


Lighting designer:
Atelier Coup d'Eclat

Architect:
Agence Philippe Hamelin

Delivery:
December 2017

Products :
120 PLR1

NOWATT
LIGHTING



Place des Prêcheurs
Marking « water drops effect »
Aix-en-Provence - France

Lighting designer:
Atelier Jéol

Landscaper:
Agence Guillermin

Delivery:
August 2019

Products:
279 PLRE2-3

NOWATT
LIGHTING



Place des Prêcheurs
Marking « water drops effect »
Aix-en-Provence - France


Lighting designer:
Atelier Jéol

Landscaper:
Agence Guillermin

Delivery:
August 2019

Products:
279 PLRE2-3

NOWATT
LIGHTING



Quai le long de la Loire
Marking the way
Brive Charensac - France

Lighting designer:
Luminescence

Landscaper:

Delivery:
August 2018

Products:
26 PLRE4

NOWATT
LIGHTING



**Marking the access path to the
Cityhall**
Ensùès La Redonne – France

Lighting designer:

Landscaper:

Delivery:
May 2019

Products:
13 PLRE4

**NOWATT
LIGHTING**



**Project La Ciotat
Forecourt Gare SNCF
La Ciotat - FRANCE**



Lighting designer:

Landscaper:

Delivery:
September 2019

Products:
18 PLRE4

**NOWATT
LIGHTING**



The enlightened river
Clermont-Ferrand - France

Lighting designer: Dominique
Colinot. City of Clermont.

Landscaper: City of Clermont

Delivery:
June 2019

Products:
200 PLRE5

NOWATT
LIGHTING



VIDEO:
CLICK HERE

The enlightened river
Clermont-Ferrand - France


Lighting designer: Dominique
Colinot. City of Clermont.

Landscaper: City of Clermont

Delivery:
June 2019

Products:
200 PLRE5

NOWATT
LIGHTING



Cycling track
Etang de Thau France

Lighting designer: Cabinet Ilex
– Aurélie Le Bouroulec

Landscaper: Ilex

Delivery:
October 2019

Products:
600 PLRE2

NOWATT
LIGHTING



Cycling track
Etang de Thau France

Lighting designer: Cabinet Ilex
– Aurélie Le Bouroulec

Landscaper: Ilex

Delivery:
October 2019

Products:
600 PLRE2

NOWATT
LIGHTING



LIGHTING
ONYX PROJECTORS
PROJECTS



Réalisation :
Le Jardin Clamart
Petit Arbois

Le Jardin Clamart
Petit Arbois France

Concepteur Lumière:

Paysagiste:

Livraison :

Produits :

**NOWATT
LIGHTING**



Lighting a path
Mezidon-Canon France

Lighting designer: Agence
Noctiluca

Landscaper:

Delivery:
June 2017

Products:
Onyx projector


NOWATT
LIGHTING



Solar Lighting
First area of Urban Art



LIGHTING
ONYX BOLLARDS
PROJECTS



Lighting an access path to the car park
Blanquefort France

Lighting designer:

Landscaper:

Delivery:
October 2019

Products:
Onyx bollards

NOWATT
LIGHTING



Lighting an access path to the car park
Roussillon France

Lighting Designer:

Landscaper:

Delivery:
May 2019

Products:
Onyx bollards

NOWATT
LIGHTING



**Lighting an access path to a residence
Sydney - Canada**

Lighting designer:

Landscaper:

Delivery:
May 2019

Products:
Onyx bollards

**NOWATT
LIGHTING**



Installation of a USB bollard
Venenles France

Lighting designer:

Landscaper:

Delivery:
February 2019

Products:
USB bollards

NOWATT
LIGHTING





LIGHTING
E-ONYX STUD
PRESENTATION

Solar luminaire created to illuminate trees, palm trees without the need to make trenches or create electrical networks. So without the risk of sealing the electrical connections and without destroying the existing plantations.



The LED and solar technologies implemented facilitate your landscape lighting projects. Thanks to its Bluetooth control, you choose the shades of white adapted to your project and you program your lighting duration.

Good light, but without wasting energy.


E-ONYX STUD

IMBEDDED LUMINAIRE
WITH SOLAR LED





E-Onyx Stud
Integrated in a concrete device



LIGHTING
ONYX COLUMN
PRESENTATION

THE TECHNOLOGICAL LEAP OF SOLAR

SOLAR CELLS

Use of Back Contact cells.
Efficiency **24%**.
85% of production still preserved after **25 YEARS** of use.

BATTERIES

The use of LiFePO4 batteries 8000 cycles at 50% DOD.
Lifespan greater than **20 YEARS** of use.


COMPONENTS & SOFTWARES

The use of microprocessors, of MPPT and algorithms to optimize the Watts produced by the cells.

LEDS

Latest generation of Leds achieving an efficiency ratio of **215 lumens/Watt** for a white 3000K, thanks to binning and our low intensity steering.

The efficiency of our solar lighting devices is boosted by the efficiency gains of their different components.



Trame: 128 x 64 Points

E_{moy} [lx]
13

E_{min} [lx]
5.48

E_{max} [lx]
32

E_{min} / E_{moy}
0.431

E_{min} / E_{max}
0.172


COURBES ISOLUX

NOWATT
LIGHTING

PARIS

INTERDISTANCE 20 M - PATH WIDTH 4M, 4M HIGH COLUMN, PRESENCE DETECTION -
13 LUX IN AVERAGE

norm EN 13201.1



[Click here to read
the Cycleways
Booklet](#)



Columns from 3 to 5 meters

NOWATT
LIGHTING



Columns
from 3 to
5 meters



**POWERING
E-ONYX POWER
PROJECTS**



Projet Pépite
Mons en Baroeul France

Lighting designer: Noctiluca -
Rozenn Lecouillard


Architect:

Delivery:
September 2018

Products :
75 sets with
1 Onyx Power
1 Lumteam 5° 4 Leds W



**NOWATT
LIGHTING**








**NOWATT
LIGHTING**

NOVELTIES

NEW LINE


SOLAR MARKING FIREFLY



**NOWATT
LIGHTING**



NEW LINE



WALLS AND FLOORS




Front lighting elements - recessed, semi-recessed, or surface-mounted


Front lighting elements - recessed, semi-recessed, or surface-mounted





Grazing lighting elements -
surface installation





OTHER PRODUCTIONS



Place d'Italie
Paris France

Lighting designer:
Agathe Argod

Landscaper:

Delivery:
September 2019

Products:
500 Glass Lens



Place d'Italie
Paris France

Lighting designer:
Agathe Argod

Landscaper:

Delivery:
September 2019

Products:
500 Glass Lens

NOWATT
LIGHTING



Place d'Italie
Paris France

Lighting designer:
Agathe Argod

Landscaper:

Delivery:
September 2019

Products:
500 Glass Lens

APPENDICES

LIFESPAN ET MAINTENANCE BENEFITS




Batteries LiFePO4: batteries Lithium Iron Phosphate

Lithium Iron Phosphate (LFP or LiFePO4):

Lithium Ferro Phosphate technology (also known as LFP or LiFePO4), which appeared in 1996, is replacing other battery technologies because of its technical advantages and **very high level of safety**.

Due to its high power density, this technology is used in medium-power traction applications ([robotics](#), [AGV](#), [E-mobility](#), [last mile delivery](#), etc.) or heavy-duty traction applications (marine traction, industrial vehicles, etc.)



The long service life of the LFP and the possibility of deep cycling make it possible to use LiFePO4 in energy storage applications ([stand-alone applications](#), [Off-Grid systems](#), [self-consumption with battery](#)) or [stationary storage](#) in general.

Major advantages of Lithium Iron Phosphate:

- Very safe and secure technology (No Thermal Runaway)
- Very low toxicity for environment (use of iron, graphite and phosphate)
- Calendar life > 10 ans
- Cycle life : from 2000 to several thousand (see chart below)
- Operational temperature range :up to 70°C
- Very low internal resistance. Stability or even decline over the cycles.
- Constant power throughout the discharge range
- Ease of recycling


Life-cycle of Lithium Iron Phosphate technology (LiFePO4)

Lithium Iron Phosphate technology is that which allows the greatest number of charge / discharge cycles. That is why this technology is mainly adopted in stationary energy storage systems (self-consumption, Off-Grid, UPS, etc.) for applications requiring long life.

The actual number of cycles that can be performed depends on several factors:

- Quality of Lithium Cell
- Level of power in C-Rate (1C rate means full discharge or charge in 1 hour, 2C is the same but in half an hour)
- Depth of Discharge (DOD)
- Operational environment : temperature, humidity, etc.

Below chart shows the estimated number of cycles for our Lithium Iron Phosphate battery cells (LFP, LiFePO4) according to the discharge power and DOD figures. The test conditions are those of a laboratory (constant temperature of 25 ° C, constant charge and discharge power).



In standard environment, and for 1C cycles, we can get from the chart the below life cycle estimation for LFP :

- 3 000 cycles at 100% DoD
- 4 500 cycles at 80% DoD
- 10 000 cycles at 60% DoD
- etc.

Nowatt works with oversized batteries. This decreases our DoD to 55% 9 months out of 12. This gives an expected lifespan of over 20 years

It should be noted that following the number of completed cycle, the batteries still have a nominal capacity > 80% of the original capacity.

Panneaux solaires SunPower Backcontact

SunPower® Complete Confidence Panel Warranty		Conventional Solar Panel Warranties ⁶
Product		
Panel	25 Years	10 Years
 Power	Performance Panels	
Year 0	97%	97%
Yearly decline	0.6%	0.7%
Year 25	82.6%	80.2%
Service ⁷		
Shipping - old panel	Yes	No ⁸
Shipping - new panel	Yes	No ⁹
Installation - new panel ¹⁰	Yes	No

Maintenance

During maintenance operations, you just have to unscrew the fixing screws and change the defective or damaged components *.

They are interconnected by easily removable waterproof automotive connectors.

* (Electronic card, batteries, solar modules)

Advantages of solar

1 / The environmental impact of solar lighting.

No power consumption

No work, no ducts and cables with a high environmental impact

2 / The quality of the devices

Today, the products made in Europe illuminate all year round.

Guaranteed lighting 365 nights

3 / The aesthetics of the devices

Now there are real architectural lighting solutions

4 / The Nowatt Intellightgence

-Our devices are equipped with microprocessors and sensors allowing them to learn where they are installed

-They are connected individually or gathered in radio frequency allowing their piloting easily

-They can be interfaced with DMX solutions

INSTALLATION MANUAL

ROUND CRYSTAL STUDS

- A. Concrete floor**
 - 1 - Poured concrete, paving stones, slabs
 - 2 - Pouring concrete
- B. Coated soil**
- C. Facade**
- D. Gravel**
- E. Caillebottis**
- F. Large pebbles**
- G. Gabion**
- H. Flood zone**
- I. Tropical zone**



A. SUBSTRATE : POURED CONCRETE, PAVING STONES, SLABS

Step 1: Make the cavity with core drill diam: 130



Make a core hole of 130 mm in diameter for a minimum depth of 95 mm.

Step 2: Remove the carrot, otherwise remove it with a perforator.
Then position the pedestal with a suction cup.



Step 3: Régler la hauteur du plot



Pour a resting mortar (if rolling space) or fill with sand according to the following two configurations:

Flush stud:

$$H \text{ (mortar height)} = D \text{ (coring depth)} - 75\text{mm}$$

Stud protruding from the height of the collar:

$$H \text{ (mortar height)} = D \text{ (core drilling depth)} - 60\text{mm}$$

Step 4: Adjust flush or horizontality



**Step 5: Fill the vertical cavity up to 2 cm before the finished floor (sand or mortar).
Pack well.**



At the end of this step if you fear vandalism you can make a silicone or polyurethane-based gasket that will bond the stud to the cavity.

Step 6: Make finishing mortar (rather liquid, match the sand to the color of the ground)




Step 7: Clean, let dry the gasket 24 hours.
That's it, next.




B. SUBSTRATES: COATED SOIL, BITUMEN, ASFALT


Step 1: Make a 122/130 mm diameter coring.
90 mm depth if flush stud.




Step 2: Pour a resting mortar over 1 to 1,5 cm.
Make a template to reproduce it easily.




Step 3: apply the primer




Step 4: Apply Sykaflex on the bottom of the stud
Only on the metal background.



Step 5: Set the stud with a suction cup.



Step 6: Make a finishing silicone seal (matching the color of the asphalt)




C. FIXING DEVICE – SURFACE FACADE

Glass protruding
Height: 62 mm



Flush glass
Height: 75 mm



Stainless steel fixing for PLR stud
Low flange
Maintained by 3 M4 screws



Two possible heights:
Tube height: 62 mm
Tube height: 75 mm

Soil type:
Gravel
Stabilized

This device is screwed onto concrete blocks


Fixing the stud in the device

D. FIXING DEVICE – GRAVEL GROUND

Glass protruding
Height: 62 mm



Flush glass
Height: 75 mm



Stainless steel fixing for PLR stud
Low flange
Maintained by 3 M4 screws



Two possible heights:
Tube height: 62 mm
Tube height: 75 mm

Soil type:
Gravel
Stabilized

This device is screwed onto concrete blocks


Fixing the stud in the device

E. FIXING DEVICE - CAILLEBOTIS

Glass protruding
Height: 62 mm




Flush glass
Height: 75 mm




Stainless steel fixing for PLR stud
Low flange
Maintained by 3 M4 screws

Two possible heights:
Tube height: 62 mm
Tube height: 75 mm

Fixing the stud in the device



F. FIXING DEVICES – LARGE PEBBLES



1- Use 140 mm PVC tubes. Cut lengths equal to the depth of the installation of the rollers.

2- Check that your stud is in OFF mode. Then install it at the end of the tube.


3- Fill the PVC tube with mortar or concrete.

4- Pour the polyurethane mastic of the color of your choice (white, gray or black), ref. : PU BOND 40 ATE VITRATEC, between the stud and the PVC tube. Smooth the gasket using a plastic spatula previously moistened.

Drying time = 20mins


5- Integrate the tube and the stud in the stones of the gabion.

Then put the stud in ON mode according to the instructions.



The material needed for the installation:
- PVC tube
- Resting mortar

G. FIXING DEVICES - GABION



1- Use 140 mm PVC tubes. Cut lengths equal to the depth of the installation of the rollers.

2- Check that your stud is in OFF mode. Then install it at the end of the tube.


3- Fill the PVC tube with mortar or concrete.

4- Pour the polyurethane mastic of the color of your choice (white, gray or black), ref. : PU BOND 40 ATE VITRATEC, between the stud and the PVC tube. Smooth the gasket using a plastic spatula previously moistened.

Drying time = 20mins

5- Integrate the tube and the stud in the stones of the gabion.

Then put the stud in ON mode according to the instructions.



The material needed for the installation:
- PVC tube
- Resting mortar

H. FLOOD ZONES



For situations where the studs could be covered with water for several hours a day, we recommend:


Provide drainage for the cavity.



And use our stainless steel fastening device with or without a collar and fill the device with polyurethane.

I. TROPICAL ZONES

We suggest the use of our tropicalized stud.



Outdoor LED marking device RGB + W
Led Nichia RGB NSSM124 +
Led Luxeon 3014 white 4000K IRC 80

15 mm thick tempered glass frame 4500 mAh LiFePO4 battery integrated in a stainless steel tube with thermal insulation of the battery
Custom Sunpower Back Contact solar panel with MPPT technology

Algorithmic management by microprocessor guaranteeing:
- charging management and calculation of optimum power all year round, taking into account the latitude, the season and the weather conditions
- management of battery usage temperatures for increased lifespan



**NOWATT
LIGHTING**


BRIEVE STORY OF SHADE

Main characteristic of a project with solar studs:


The studs are in most cases placed on the ground. They can be in the shade more easily than a solar device installed in height....

We must therefore assess the possible shade areas and estimate their duration.

For this, it is necessary to know the apparent movements of the sun and the resulting cast shadows.



Apparent movement of the sun in summer in France





WATT
LIGHTING

contact@nowatt-lighting.com

(+ 33) 04 91 02 17 06

1 rue Guy Moquet,
13001 Marseille

NOWATT
LIGHTING